


**Built-in SRAM
SERIAL-INTERFACE REAL TIME CLOCK MODULE**

RX-4581 NB

- Built in frequency adjusted 32.768 kHz crystal unit.
- Interface Type : 4-wire serial interface
- Operating voltage range : 1.6 V to 5.5 V
- Wide Timekeeper voltage range : 1.6 V to 5.5 V
- Low backup current : 0.4 μ A / 3 V (Typ.)
- Built-in SRAM : Built-in 128 bit (8 bit \times 16) RAM.
- 32.768 kHz frequency output function : C-MOS output With Control Pin
- The various functions include full calendar, alarm, timer.



Product Number (Please contact us)
RX-4581NB : Q41458192000200




Actual size



Block diagram

Overview




- **Built-in SRAM**
 - Include 128 bit (8 bit \times 16) RAM.
- **Interface Type**
 - Serial interface in 4 lines form.
 - It is possible to make it to 3 lines by wired-OR connecting DI and DO pins.
- **32.768 kHz frequency output function**
 - FOUT pin output (C-MOS output), CL=30 pF
 - FOE pin enables output on/off control.
- **Timer function**
 - Timer function can be set up between 1/4096 second and 4095 minutes.
 - It is recorded automatic to TF-bit at the time of event occurrence, and possible to output with /TIRQ pin output (open-drain output).
- **Interrupt function**
 - Alarm interrupt function, and timer interrupt function.

Pin Function

Terminal connection / External dimensions

(Unit:mm)

| Signal Name | Input/Output | Function |
|-------------|--------------|--|
| CE0 | Input | The chip enabled input pin 0. (It has a built -in pull-down resistance) |
| CE1 | Input | The chip enabled input pin 1. (It does not have a built -in pull-down resistance) |
| CLK | Input | The shift clock input pin for serial data transfer. |
| DI | Input | The data input pin for serial data transfer. |
| DO | Output | The data output pin for serial data transfer. |
| FOUT | Output | This pin outputs the reference clock signal at 32.768 kHz (CMOS output). High impedance at the time of output off. |
| FOE | Input | The input pin for the FOUT output control. |
| /AIRQ | Output | The open drain output pin for alarm and time update interrupts. |
| /TIRQ | Output | The open drain output pin for timer interrupt. |
| VDD | — | Connected to a positive power supply. |
| GND | — | Connected to a ground. |



The metal case inside of the molding compound may be exposed on the top or bottom of this product. This purely cosmetic and does not have any effect on quality, reliability or electrical specs.

Specifications (characteristics)

* Refer to application manual for details.

Recommended Operating Conditions

| Item | Symbol | Conditions | Min. | Typ. | Max. | Unit |
|-----------------------|--------|------------|------|------|------|------|
| Power voltage | VDD | — | 1.6 | 3.0 | 5.5 | V |
| Clock voltage | VCLK | — | 1.6 | 3.0 | 5.5 | V |
| Operating temperature | TOPR | — | -40 | +25 | +85 | °C |

Frequency characteristics

| Item | Symbol | Conditions | Rating | Unit |
|---------------------------|--------------|----------------------------|--------------|------------------|
| Frequency tolerance | $\Delta f/f$ | Ta = +25 °C VDD = 3.0 V | 5 \pm 23 * | $\times 10^{-6}$ |
| Oscillation start-up time | tSTA | Ta = +25 °C VDD = 3.0 V | 3 Max. | s |

* Please ask for tighter tolerance. (Equivalent to 1 minute of monthly deviation)

Current consumption characteristics

Ta = -40 °C to +85 °C

| Item | Symbol | Conditions | Min. | Typ. | Max. | Unit |
|---------------------|--------|--|-----------|------|------|---------|
| Current Consumption | IBK | CE0, CE1 = GND FOE = GND | VDD = 5 V | 0.6 | 1.2 | μ A |
| | | FOUT ;output OFF (Hi - z) | VDD = 3 V | 0.4 | 0.8 | |
| | I32k | CE0, CE1 = GND FOE = VDD | VDD = 5 V | 8.0 | 20.0 | μ A |
| | | FOUT ; 32.768 kHz output ON CL = 30 pF | VDD = 3 V | 5.0 | 12.0 | |

PROMOTION OF ENVIRONMENTAL MANAGEMENT SYSTEM CONFORMING TO INTERNATIONAL STANDARDS

At Seiko Epson, all environmental initiatives operate under the Plan-Do-Check-Action (PDCA) cycle designed to achieve continuous improvements. The environmental management system (EMS) operates under the ISO 14001 environmental management standard.

All of our major manufacturing and non-manufacturing sites, in Japan and overseas, completed the acquisition of ISO 14001 certification.

ISO 14000 is an international standard for environmental management that was established by the International Standards Organization in 1996 against the background of growing concern regarding global warming, destruction of the ozone layer, and global deforestation.




WORKING FOR HIGH QUALITY

In order provide high quality and reliable products and services than meet customer needs,

Seiko Epson made early efforts towards obtaining ISO9000 series certification and has acquired ISO9001 for all business establishments in Japan and abroad. We have also acquired ISO/TS 16949 certification that is requested strongly by major automotive manufacturers as standard.

ISO/TS16949 is the international standard that added the sector-specific supplemental requirements for automotive industry based on ISO9001.

► Explanation of the mark that are using it for the catalog

| | |
|---|---|
|  | <p>► Pb free.</p> |
|  | <p>► Complies with EU RoHS directive. *About the products without the Pb-free mark. Contains Pb in products exempted by EU RoHS directive. (Contains Pb in sealing glass, high melting temperature type solder or other.)</p> |
|  | <p>► The products have been designed for high reliability applications such as Automotive.</p> |

Notice

- This material is subject to change without notice.
- Any part of this material may not be reproduced or duplicated in any form or any means without the written permission of Seiko Epson.
- The information about applied circuitry, software, usage, etc. written in this material is intended for reference only. Seiko Epson does not assume any liability for the occurrence of infringing on any patent or copyright of a third party. This material does not authorize the licensing for any patent or intellectual copyrights.
- When exporting the products or technology described in this material, you should comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations.
- You are requested not to use the products (and any technical information furnished, if any) for the development and/or manufacture of weapon of mass destruction or for other military purposes. You are also requested that you would not make the products available to any third party who may use the products for such prohibited purposes.
- These products are intended for general use in electronic equipment. When using them in specific applications that require extremely high reliability, such as the applications stated below, you must obtain permission from Seiko Epson in advance.
 - / Space equipment (artificial satellites, rockets, etc.) / Transportation vehicles and related (automobiles, aircraft, trains, vessels, etc.) / Medical instruments to sustain life / Submarine transmitters / Power stations and related / Fire work equipment and security equipment / traffic control equipment / and others requiring equivalent reliability.
- All brands or product names mentioned herein are trademarks and/or registered trademarks of their respective.